



Q1.

- 2 (a) (i) distance from a (fixed) point..... M1
 in a specified direction A1
 (Allow 1 mark for 'distance in a given direction')
- (ii) (displacement from start is zero if) car at its starting position..... B1 [3]
- (b) (i) $v^2 = u^2 + 2as$
 $28^2 = 2 \times a \times 450$ (use of component of 450 scores no marks).... C1
 $a = 0.87 \text{ m s}^{-2}$ A1 [2]
 (-1 for 1 sig. fig. but once only in the question)
- (ii) $v = u + at$ or any appropriate equation
 $28 = 0.87t$ or appropriate substitution..... C1
 $t = 32 \text{ s}$ A1 [2]
- (iii) $E_k = \frac{1}{2}mv^2$ C1
 $= \frac{1}{2} \times 800 \times 28^2$
 $= 3.14 \times 10^5 \text{ J}$ A1 [2]
- (iv) $E_p = mgh$ C1
 $= 800 \times 9.8 \times 450 \sin 5$ C1
 $= 3.07 \times 10^5 \text{ J}$ A1 [3]
- (ii) power = energy/time C1
 $=(6.21 \times 10^5)/32.2$ C1
 $= 1.93 \times 10^4 \text{ W}$ A1 [3]
 (power = Fv with $F = mg \sin \theta$ scores no marks)
- (iii) some work also done against friction forces..... M1
 location of frictional forces/identified A1 [2]

(allow reasonable alternatives)

Q2.

- 5 (a) (i) distance = $2\pi nr$ B1
 (ii) work done = $F \times 2\pi nr$ (accept e.c.f.) B1 [2]
- (b) total work done = $2 \times F \times 2\pi nr$ B1
 but torque $T = 2Fr$ B1
 hence work done = $T \times 2\pi n$ A0 [2]
- (c) power = work done/time ($= 470 \times 2\pi \times 2400)/60$)
 $= 1.2 \times 10^5 \text{ W}$ A1 [2]
- Total [6]

Q3.



3	(a) (i) $\Delta E_p = mgh$ = $0.602 \times 9.8 \times 0.086$ = 0.51 J (do not allow $g = 10$, $m = 0.600$ or answer 0.50 J)	C1 A1 [2]
	(ii) $v^2 = (2gh) = 2 \times 9.8 \times 0.086$ or $(2 \times 0.51)/0.602$ $v = 1.3 \text{ (m s}^{-1}\text{)}$	M1 A0 [1]
(b)	$2 \times V = 602 \times 1.3$ (allow 600) $V = 390 \text{ m s}^{-1}$	C1 A1 [2]
(c) (i)	$E_k = \frac{1}{2}mv^2$ = $\frac{1}{2} \times 0.002 \times 390^2$ = 152 J or 153 J or 150 J	C1 A1 [2]
	(ii) E_k not the same/changes or E_k before impact > E_k after/ E_p after so must be inelastic collision (allow 1 mark for 'bullet embeds itself in block' etc.)	M1 A1 [2]

Q4.

4 (a) (i)	(change in) potential energy = mgh = $0.056 \times 9.8 \times 16$ = 8.78 J (allow 8.8)	C1 A1 [2]
(ii)	(initial) kinetic energy = $\frac{1}{2}mv^2$ = $\frac{1}{2} \times 0.056 \times 18^2$ = 9.07 J (allow 9.1) total kinetic energy = $8.78 + 9.07 = 17.9 \text{ J}$	C1 C1 A1 [3]
(b)	kinetic energy = $\frac{1}{2}mv^2$ $17.9 = \frac{1}{2} \times 0.056 \times v^2$ and $v = 25(.3) \text{ m s}^{-1}$	B1 [1]
(c)	horizontal velocity = 18 m s^{-1}	B1 [1]
(d) (i)	correct shape of diagram (two sides of right-angled triangle with correct orientation)	B1
(ii)	angle = $41^\circ \rightarrow 48^\circ$ (allow trig. solution based on diagram) (for angle $38^\circ \rightarrow 41^\circ$ or $48^\circ \rightarrow 51^\circ$, allow 1 mark)	A2 [3]

Q5.



MEGA LECTURE

- 3 (a) either energy (stored)/work done represented by area under graph
 or energy = average force × extension

$$\text{energy} = \frac{1}{2} \times 180 \times 4.0 \times 10^{-2}$$

$$= 3.6 \text{ J}$$
 B1
 C1
 A1 [3]
- (b) (i) either momentum before release is zero M1
 so sum of momenta (of trolleys) after release is zero A1
 or force = rate of change of momentum (M1)
 force on trolleys equal and opposite (A1)
 or impulse = change in momentum (M1)
 impulse on each equal and opposite (A1) [2]
- (ii) 1 $M_1 V_1 = M_2 V_2$ B1 [1]
 2 $E = \frac{1}{2} M_1 V_1^2 + \frac{1}{2} M_2 V_2^2$ B1 [1]
- (iii) 1 $E_K = \frac{1}{2} m v^2$ and $p = m v$ combined to give M1
 $E_K = p^2 / 2m$ A0 [1]
 2 m smaller, E_K is larger because p is the same/constant M1
 so trolley B A0 [1]

Q6.

- 2 (a) work done is the force × the distance moved / displacement in the direction of the force
 or
 work is done when a force moves in the direction of the force B1 [1]
- (b) component of weight = $850 \times 9.81 \times \sin 7.5^\circ$
 $= 1090 \text{ N}$ C1
 (use of incorrect trigonometric function, 0/2) A1 [2]
- (c) (i) $\Sigma F = 4600 - 1090 = 3510$
 deceleration = $3510 / 850$
 $= 4.1 \text{ ms}^{-2}$ M1
 A1 A0 [2]
- (ii) $v^2 = u^2 + 2as$
 $0 = 25^2 + 2 \times -4.1 \times s$
 $s = 325 / 8.2$
 $= 76 \text{ m}$ C1
 (allow full credit for calculation of time (6.05 s) & then s) A1 [2]
- (iii) 1. kinetic energy = $\frac{1}{2} m v^2$
 $= 0.5 \times 850 \times 25^2$
 $= 2.7 \times 10^5 \text{ J}$ C1
 A1 [2]
2. work done = 4600×75.7
 $= 3.5 \times 10^5 \text{ J}$ A1 [1]
- (iv) difference is the loss in potential energy (owtpe) B1 [1]

Q7.

3 (a) evidence of use of area below the line distance = 39 m (allow $\pm 0.5\text{m}$) (if $> \pm 0.5\text{m}$ but $\leq 1.0\text{m}$, then allow 1 mark)	B1 A2	[3]
(b) (i) 1 $E_K = \frac{1}{2}mv^2$ $\Delta E_K = \frac{1}{2} \times 92 \times (6^2 - 3^2)$ = 1240 J	C1 A1	[2]
2 $E_P = mgh$ $\Delta E_P = 92 \times 9.8 \times 1.3$ = 1170 J	C1 A1	[2]
(ii) $E = Pt$ $E = 75 \times 8$ = 600 J	C1 A1	[2]
(c) (i) energy = $(1240 + 600) - 1170$ = 670 J	M1 A0	[1]
(ii) force = $670/39 = 17\text{N}$	A1	[1]
(d) frictional forces include air resistance air resistance decreases with decrease of speed	B1 B1	[2]

Q8.

3 (a) (i) work done equals force \times distance moved / displacement in the direction of the force	B1	[1]
(ii) power is the rate of doing work / work done per unit time	B1	[1]
(b) (i) kinetic energy = $\frac{1}{2}mv^2$ = $0.5 \times 600 (9.5)^2$ = 27075 (J) = 27 kJ	C1 C1 A1	[3]
(ii) potential energy = mgh = $600 \times 9.81 \times 4.1$ = 24132 (J) = 24 kJ	M1 A1 A0	[2]
(iii) work done = $27 - 24 = 3.0\text{ kJ}$	A1	[1]
(iv) resistive force = $3000 / 8.2$ (distance along slope = $4.1 / \sin 30^\circ$) = 366 N	C1 A1	[2]

Q9.



2 (a) (i)	$v^2 = u^2 + 2as$ $= (8.4)^2 + 2 \times 9.81 \times 5$ $= 12.99 \text{ ms}^{-1}$ (allow 13 to 2 s.f. but not 12.9)	C1 A1	[2]
(ii)	$t = (v - u) / a$ or $s = ut + \frac{1}{2}at^2$ $= (12.99 - 8.4) / 9.81$ or $5 = 8.4t + \frac{1}{2} \times 9.81t^2$ $t = 0.468 \text{ s}$	M1 A0	[1]
(b)	reasonable shape suitable scale correctly plotted 1 st and last points at (0,8.4) and (0.88 – 0.96,0) with non-vertical line at 0.47 s	M1 A1 A1	[3]
(c) (i)	1. kinetic energy at end is zero so $\Delta KE = \frac{1}{2}mv^2$ or $\Delta KE = \frac{1}{2}mu^2 - \frac{1}{2}mv^2$ $= \frac{1}{2} \times 0.05 \times (8.4)^2$ $= (-) 1.8 \text{ J}$	C1 A1	[2]
	2. final maximum height = $(4.2)^2 / (2 \times 9.8) = (0.9 \text{ m})$ change in PE = $mgh_2 - mgh_1$ $= 0.05 \times 9.8 \times (0.9 - 5)$ $= (-) 2.0 \text{ J}$	C1 C1 A1	[3]
(ii)	change is – 3.8 (J) energy lost to ground (on impact) / energy of deformation of the ball / thermal energy in ball	B1 B1	[2]

Q10.

3 (a)	loss in potential energy due to decrease in height (as P.E. = mgh) gain in kinetic energy due to increase in speed (as K.E. = $\frac{1}{2}mv^2$) <i>special case 'as PE decreases KE increases' (1/2)</i> increase in thermal energy due to work done against air resistance loss in P.E. equals gain in K.E. and thermal energy	(B1) (B1) (B1) (B1) max. 3	[3]
(b) (i)	kinetic energy = $\frac{1}{2}mv^2$ $= \frac{1}{2} \times 0.150 \times (25)^2$ $= 46.875 = 47 \text{ J}$	C1 C1 A1	[3]
(ii) 1.	potential energy (= mgh) = $0.150 \times 9.81 \times 21$ loss = KE – mgh = $46.875 - (30.9)$ $= 15.97 = 16 \text{ J}$	C1 C1 A1	[3]
2.	work done = 16J work done = force × distance $F = 16 / 21 = 0.76 \text{ N}$	C1 A1	[2]

Q11.


MEGA LECTURE

- 4 (a) force \times distance moved M1
 in the direction of the force A1 [2]
- (b) weight / force = mg M1
 $\Delta E_p = mg \times \Delta h$ A1 [2]
 (no marks for quote of $mg\Delta h$)

Q12.

- 8 (a) product of force and distance
 moved in the direction of the force M1
 A1 [2]
- (b) (i) falls from rest
 decreasing acceleration
 reaches a constant speed B1
 B1
 B1 [3]
- (ii) straight line with negative gradient
 y-axis intercept above maximum E_k
 reasonable gradient (same magnitude as that for E_k initially) B1
 B1
 B1 [3]

Q13.

- 1 (a) (i) product of force and distance moved
 (by force) in the direction of the force M1
 A1 [2]
- (ii) work (done) per unit time (*idea of ratio needed*) B1 [1]
- (b) either work/time or power = (force \times distance)/time
 to give power = force \times velocity M1
 A1 [2]
- (c) (i) kinetic energy ($= \frac{1}{2}mv^2$) = $\frac{1}{2} \times 1900 \times 27^2$
 power = $692550 / 8.1 = 8.55 \times 10^4$ W C1
 A1 [2]
- (ii) either for equal increments of speed, increments of E_k are different
 so longer time (to increase speed) at high speeds M1
 A1 [2]
- or air resistance increases with speed (M1)
 so driving force (and acceleration) reduced (A1)
- or $P (= Fv) = mav$ (M1)
 (P and m constant) so when v increases, a decreases (A1)

Q14.



- 3 (a) (i) potential energy: stored energy available to do work B1 [1]
- (ii) gravitational: due to height/position of mass OR distance from mass
OR moving mass from one point to another
elastic: due to deformation/stretching/compressing B1 [2]
- (b) (i) height raised = $(61 - \{61 \cos 18\}) = 3.0 \text{ cm}$
energy = $(mgh = 0.051 \times 9.8 \times 0.030 =) 1.5 \times 10^{-2} \text{ J}$ C1
A1 [2]
- (ii) moment = force \times perpendicular distance
 $= 0.051 \times 9.8 \times 0.61 \times \sin 18$
 $= 0.094 \text{ N m}$ C1
A1 [2]

Q15.

- 4 (a) electrical potential energy (stored) when charge moved and gravitational potential energy (stored) when mass moved
due to work done in electric field and work done in gravitational field B1
B1 [2]
- (b) work done = force \times distance moved (in direction of force)
and force = mg
 $mg \times h$ or $mg \times \Delta h$ M1
A1 [2]
- (c) (i) $0.1 \times mgh = \frac{1}{2}mv^2$
 $0.1 \times m \times 9.81 \times 120 = 0.5 \times m \times v^2$
 $v = 15.3 \text{ ms}^{-1}$ B1
B1
A0 [2]
- (ii) $P = 0.5 m v^2 / t$
 $m / t = 110 \times 10^3 / [0.25 \times 0.5 \times (15.3)^2]$
 $= 3740 \text{ kg s}^{-1}$ C1
C1
A1 [3]

Q16.



- 3 (a) (i) power = work done per unit time / energy transferred per unit time / rate of work done
B1 [1]
- (ii) Young modulus = stress / strain
B1 [1]
- (b) (i) 1. $E = T / (A \times \text{strain})$ (allow strain = ϵ)
 $T = E \times A \times \text{strain} = 2.4 \times 10^1 \times 1.3 \times 10^{-4} \times 0.001$
 $= 3.12 \times 10^4 \text{ N}$
C1
M1
A0 [2]
2. $T - W = ma$
 $[3.12 \times 10^4 - 1800 \times 9.81] = 1800a$
 $a = 7.52 \text{ ms}^{-2}$
C1
C1
A1 [3]
- (ii) 1. $T = 1800 \times 9.81 = 1.8 \times 10^4 \text{ N}$
A1 [1]
2. potential energy gain = mgh
 $= 1800 \times 9.81 \times 15$
 $= 2.7 \times 10^5 \text{ J}$
C1
A1 [2]
- (iii) $P = Fv$
 $= 1800 \times 9.81 \times 0.55$
input power = $9712 \times (100/30) = 32.4 \times 10^3 \text{ W}$
C1
C1
A1 [3]

Q17.

- 3 (a) (work =) force \times distance moved / displacement in the direction of the force
OR when a force moves in the direction of the force work is done
B1 [1]
- (b) kinetic energy = $\frac{1}{2} mv^2$
 $= \frac{1}{2} 0.4 (2.5)^2 = 1.25 / 1.3 \text{ J}$
C1
A1 [2]
- (c) (i) area under graph is work done / work done = $\frac{1}{2} Fx$
 $1.25 = (14 x) / 2$
 $x = 0.18 \text{ (0.179) m}$ [allow $x = 0.19 \text{ m}$ using kinetic energy = 1.3 J]
C1
C1
A1 [3]
- (ii) smooth curve from $v = 2.5$ at $x = 0$ to $v = 0$ at Q
curve with increasing gradient
M1
A1 [2]

Q18.



- 4 (a) gravitational PE is energy of a mass due to its position in a gravitational field
 elastic PE energy stored (in an object) due to (a force) changing its shape /
 deformation / being compressed / stretched / strained B1
 B1 [2]
- (b) (i) 1. kinetic energy = $\frac{1}{2}mv^2$
 $= \frac{1}{2} \times 0.065 \times 16^2 = 8.3(2)$ J C1
 A1 [2]
2. $v^2 = 2gh$ OR PE = mgh
 $h = 16^2 / (2 \times 9.81) = 13(.05)$ m C1
 A1 [2]
- (iii) speed at $t = \frac{1}{2}$ total time = 8 (ms^{-1}) or total $t = 1.63$ or $t_{1/2} = 0.815$ s C1
 KE is $\frac{1}{4}$ or h at $t_{1/2} = 9.78$ (m) C1
 and PE is $\frac{3}{4}$ of max ratio = 3 or ratio = $9.78 / 3.26 = 3$ A1 [3]
- (iii) time is less because (average) acceleration is greater OR average force is greater B1 [1]

