

How to quote any physical quantity

28 September 2020 08:28

Since physical quantities have errors/uncertainty in them \therefore they are quoted as follows

$$L = 25.0 \pm 0.5 \text{ cm}$$

Actual value
OR True value
Actual error or
Actual uncertainty

general form $L = x \pm \Delta x$

fractional error = $\frac{0.5}{25.0}$ OR $\frac{\Delta x}{x}$

% error = $\frac{0.5}{25.0} \times 100$ OR $\frac{\Delta x}{x} \times 100$
= 2%

Rules \therefore ① errors to be quoted correct to 1 significant figure

② True value must be consistent with the error

eg $x = 25.00$ $\Delta x = 0.50$

$$x = 25.0 \pm 0.5 \text{ 1 s.f.}$$

eg $x = 25.000$ $\Delta x = 0.05$

$$x = 25.00 \pm 0.05 \text{ 1 s.f.}$$

eg $x = 16.00$ $\Delta x = 0.36$

$$x = 16.0 \pm 0.4 \text{ 1 s.f.}$$

① Rules for adding two physical quantities

- True values must be added
- errors/uncertainty also added

$$x = 18.5 \pm 0.5$$

$$y = 12.5 \pm 0.5$$

- write down value for $x+y$

$$x+y = 31 \pm 1$$

- write down fractional error for $x+y = \frac{1}{31}$

- write down % error in $x+y$

$$= \frac{1}{31} \times 100 = 3.2\% \text{ or } 3.22\% \text{ or } 3.226\%$$

[rule for percentages \therefore To be given to a maximum of 2 or 3 s.f.]

$$= 3.22\% \text{ or } 3.2\%$$

② Rule for subtracting two physical quantities

- True values to be subtracted

- Since errors can't get reduced \therefore errors are still added together

$$x = 18.5 \pm 0.5$$

$$y = 12.5 \pm 0.5$$

- write down value for $x-y$

$$x-y = 6 \pm 1$$

- fractional error in $x-y = \frac{1}{6}$

- % error in $x-y = \frac{1}{6} \times 100 = 17\% \text{ or } 16.7\%$

eg initial velocity = 20 m/s
final velocity = 60 m/s
both values have uncertainty of 0.5 m/s

Cal % error in change in velocity?

$$\text{Initial } 20.0 \pm 0.5 \text{ m/s}$$

$$\text{Final } 60.0 \pm 0.5 \text{ m/s}$$

$$\Delta v (\text{Change in velocity}) = \text{Final} - \text{Initial} = 40 \pm 1 \text{ m/s}$$

$$\% \text{ error in } \Delta v = \frac{1}{40} \times 100$$

$$= 2.5\% \text{ or } 2.50\% \text{ done till here}$$

③ Rule for multiplying two physical quantities

- True values to be multiplied

- In multiplication, fractional errors are added together

$$L = 5.0 \pm 0.5$$

$$B = 6.0 \pm 0.5$$

} Rectangle

- write down the Actual value for the Area of Rectangle.

- write down the error in the area

$$A = L \times B$$

fractional errors to be added

$$\frac{\Delta A}{A} = \frac{\Delta L}{L} + \frac{\Delta B}{B}$$

$$\frac{\Delta A}{30} = \frac{0.5}{5.0} + \frac{0.5}{6.0}$$

$$\Delta A = 5.5$$

$$\text{Final answer } 30 \pm 5.5$$

eg: $L = 2.0 \pm 0.5$
 $B = 18.0 \pm 0.5$
 $H = 16.0 \pm 0.5$ } Rectangular block

Cal its volume along with its uncertainty.

- True value = $V = 2 \times 18 \times 16$
 $V = 576$

- Error in volume, fractional errors are added

$$\frac{\Delta V}{V} = \frac{\Delta L}{L} + \frac{\Delta B}{B} + \frac{\Delta H}{H}$$

$$\frac{\Delta V}{576} = \frac{0.5}{2} + \frac{0.5}{18} + \frac{0.5}{16}$$

$$\Delta V = 178$$

$$600 \pm 200$$

if error is written correct to the nearest 100, than to maintain consistency the true value must also be rounded off to the nearest 100. (hence 576 changed to 600).

Q True value = 327.65

error = 9.8

quote this physical quantity along with its uncertainty?

$$x = 330 \pm 10$$

Q $V = L^2 \times H$

How would you write down this formula in the form of fractional errors?

$$\frac{\Delta V}{V} = 2 \frac{\Delta L}{L} + \frac{\Delta H}{H}$$

- The power with any term can be written down as a multiplying constant.

Q $V = L^3 \times H^2 \times \sqrt{T}$

fractional error would be written as

$$\frac{\Delta V}{V} = 3 \frac{\Delta L}{L} + 2 \frac{\Delta H}{H} + \frac{1}{2} \frac{\Delta T}{T}$$

④ Rule for dividing Physical quantities

- True values to be divided

- fractional errors to be added

eg $d = 40.0 \pm 0.1 \text{ m}$
 $t = 2.50 \pm 0.05 \text{ s}$

Cal speed along with its uncertainty?

$$s = d/t = 16$$

$$\Delta s = 0.36$$

$$\Rightarrow 16.0 \pm 0.4$$